

MTSM3

Technical Machinery Notes

ROPE/EUROPE LINK MAKING & CALIBRATION MACHINE - 245

Machine for the production of Rope & Europe chain links. The unit is fed with wire on a reel. The wire can be solid or hollow (tube with a metal core). The process consists in

cutting the wire to the exact size, forming the link, hammering it for perfect calibration and brilliance and then discharging it into a waiting container, ready for use in next step.

The machine is controlled via an onboard PLC interfaced with touchscreen controller.

Ease of use is guaranteed by fixed mechanical setting for all parts requiring adjustment. The whole work process is aligned for operator ease.

Brushless motors guarantee speed and precision.



Technical features

Max. production speed 150 links/min Wire Ø 0.25 - 1.20 mm

Technical data

Voltage (single phase)

Power

Compressed air

230 V 50/60 Hz
1.30 kW
1 l/min (filtered) at 7 bar

Dimensions 90 x 45 x 152(h) cm – 80 kg

Packing 180 x 60 x 55 (h) cm 160 kg

Note. The above data, features and characteristics are not binding. CIEMMEO s.r.l. retains the right to vary them at any time without prior notice

CIEMMEO s.r.l. -Via dell'Industria, 22 - 36060 Casoni di Mussolente (VI) - ITALY - V.A.T. Code IT00621600246

Tel. +39-0424-577565 - Fax +39-0424-577563 - Video +39-0424-578017 - Email info@ciemmeo.com - WWW ciemmeo.com